



## Technical specifications

### Q-Portable Light Charger 18 Units

Product Code:	Q21NA0x
Application:	12V, Portable charger.
Input Voltage:	220-240Vac, 50-60Hz
Max Charge Current:	12A
Ripple:	300mV rms, max 0,78A
Ambient Temp.:	-20°C to +50°C
Charger Type:	4-step, Automatic
Battery Type:	12V lead-acid (WET, MF, Ca/Ca, AGM and Gel)
Ingress Protection:	IP65
Weight:	12Kg to 20kg

## Assembly

The BOL/SPAL Charging station is available for charging 6,8,12 or 18 units. The independent Charger blocks is specially designed for the Q-SPAL and Q-BOL lighting units.

## Operation

After turning on the BOL/SPAL Charging station, using the ON/OFF power switch. All the chargers will load automatic.

Fully charge the Q-SPAL and Q-BOL within 8 hours. Smart technology is for the maintenance of the batteries.

## Order Codes

In the table below the order codes are displayed.

Order Code →		Product Code		
		Q21	NA	..
<b>Product Name</b>		↑	↑	↑
Q21	BOL/SPAL Charging station	↓		
<b>Mounting</b>			↑	
NA	Portable Light Charger		↓	
<b>Zone</b>				↑
06	Charging station 6 Units			↓
07	Charging station 8 Units			
08	Charging station 12 Units			
09	Charging station 18 Units			