

Q-Aviation Lighting / Obstruction Lighting / Q-Obstruction Light Low Intensity 32 cd

Q-OBSTRUCTION LIGHT LOW INTENSITY 32 CD



TECHNICAL DETAILS

Application:	Obstruction Lighting
Classification:	Safe Area only
Light Source:	LED, steady burning
Light Colour:	Red, 630 nm
Light Intensity:	32 cd
Vertical Beam Profile:	as per CAP437/ICAO
Colour chromaticity:	as per CAP437/ICAO
Enclosure:	Aluminium, Powder coated
Mounting:	Rigid, 4x M8
Input Voltage:	1) 100-240 Vac 50-60 Hz 2) 24 Vdc
External Earthing:	up to 4mm ²
Ambient Temp:	-25° to +65°C
In Compliance With:	CAP437/ ICAO, Annex 14, Type B FAA L-810
Cable glands included:	2 x M25x1.5
Cable stops included:	1 x M25x1.5
Cable Outer Dimension:	11,1 - 20,0 mm
Consumption:	6 Watt
Life expectancy:	100.000+ hours
IP index:	IP 67
Weight:	2.20 kg.
Dimensions:	183x183x155 mm (LxWxH)
Packaging dimension:	200x200x200 mm (LxWxH)

DESCRIPTION

The Q-Obstruction Light Low Intensity 32 cd is a ICAO & CAP437 compliance Obstruction light for all facilities. The Obstruction Light is available in the configurations 100-240 Vac and 24 Vdc.

CERTIFICATES



Q81RI03 – Q-Obstruction Light Low Intensity 32 cd

- 11** Input power: 100-240 Vac
- 12** Input power: 24 Vdc

ORDER CODE

Q81RI03

11

R1

MAIN DIMENSIONS

The main dimensions and mounting are displayed dimensions in the image below:

