

Q-Aviation Lighting / Helipad Lighting / Q-WDI Unlighted, FAA L-807 Orange

Q-WDI UNLIGHTED, FAA L-807 ORANGE



TECHNICAL DETAILS

Application:	Heliport/ Airfield
Classification:	Safe Area
Assembly:	Windsock assembly
Internal Light Source:	N/A
Mast Specification:	Full Frangible, fiberglass and polyester resin, Ø140,0 pole diameter (at base) x 4 mm (wall thickness)
Mast coating:	Orange, UV resistance coating
Mounting:	Tiltable foot
Windsock Frame:	SS316. Rotating Frame and Hoop
Ambient Temp:	-25° to +65° C
In Compliance With:	FAA L-807 ICAO, Annex 14 vol. II
IP index:	N/A
Mast Length:	4.8m
Windsock colour:	Orange
Windsock sizes: (Windsock not included)	Ø30 x 120 cm - 11,8" x 3,9ft. Ø45 x 250 cm - 17,7" x 8,2ft. Ø50 x 150 cm - 19,7" x 4,9ft. Ø60 x 240 cm - 23,6" x 7,8ft. Ø90 x 366 cm - 35,4" x 12,0ft. Ø90 x 375 cm - 35,4" x 12,3ft

DESCRIPTION

The Full Frangible mast makes this wind direction indicator suitable to place near to the landing area.
If a vehicle accidentally hits this unit, the mast breaks rather than causing serious damage to the vehicle.

CERTIFICATES



ORDER CODE

Q23UL94 - Q-WDI Unlighted, L-807 Orange

Q23UL94

R1

MAIN DIMENSIONS

The main dimensions and mounting are displayed dimensions in the image below:

